

# 750 Impact Performance Report



## 2010 Brunswick 750 Impact

BOAT	
2010 Brunswick 750 Impact	
Material:	RIB
Length:	24' 7" w/Collar
Beam:	9' 4" w/Collar
Weight w/o Engine:	Approx. 3100 LBS Dry
Maximum HP:	300 HP
Fuel Capacity:	145 Gallons
Transom Height:	25" Shaft
Steering:	Hydraulic

ENGINE	
2010 Evinrude® ETEC® 150 HP TWIN	
Engine Type:	60° V6
Horsepower:	150 HP @ 5350 RPM
Displacement:	158.2 Cu. In.
Induction:	ETEC DFI
Operating Range:	4850-5850 RPM
Weight:	433 LBS Dry Weight
Gear Ratio:	1.85:1

PROPELLER	
BRP Viper™	
Material:	Stainless Steel
Diameter/Pitch:	14.75" x 19"
No. of Blades:	3
Part Number:	763918 / 763919
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
Motor Height	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.7	0.36	7.6	995
1000	5.6	1.17	4.8	621
1500	7.8	2.64	3.0	383
2000	10.8	5.48	2.0	257
2500	19.0	7.65	2.5	324
3000	26.3	10.66	2.5	321
3500	32.2	12.48	2.0	337
4000	37.5	15.85	2.4	303
4500	41.7	19.72	2.1	273
5000	47.1	27.32	1.7	225
5500	50.8	30.79	1.6	215
5725	52.4	30.84	1.7	222
Fuel Data Based on Twin Engines Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Moderate Chop
Wind Velocity:	10-20 MPH
Air Temperature:	70° F
Fuel Load:	114.5 Gal
Weight:	2 Men, Fuel, test & safety gear Harc Top with light bar

PERFORMANCE SUMMARY	
Top Speed:	52.4 MPH
Best Fuel Efficiency:	2.6 MPG with a range of 337 Miles @ 32.2 MPH
Acceleration:	3.11 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2010 BRP US Inc. All rights reserved.

™ and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.



**Brunswick Commercial and Government Products, Inc**  
 420 Megan Z Ave. Edgewater, FL 32132 Phone 386.423.2900 Fax 386.423.9187  
[www.brunswickcgp.com](http://www.brunswickcgp.com)



# 750 Impact



## Specifications


LOA	24' 7"
Beam	9' 4"
Beam inside	5' 10"
Tube diameter	1' 10"
Weight capacity	7002 lbs
Person capacity	22
Max HP	300 hp
Fuel Capacity	157 gal

## Standard Features

- Heavy-duty fiberglass hull
- Haze gray gelcoat
- Commercial-grade tubes with exclusive AKRON TPE® fabric
- Heavy duty inflation and pressure relief valves
- Bow locker
- Non-slip molded into gel coated deck and tubes
- Below-deck storage

## Well-suited for work on tough water.

The 750 Impact™ is a versatile platform that can be outfitted with either inboard or outboard power. A deep-V fiberglass hull slices through rough water and keeps the crew dry. The inflatable tubes provide superior lateral stability and are highly resistant to pollution, deterioration, and puncture. Hundreds of available options allow each Impact model to be customized to your mission.



**Brunswick Commercial and Government Products, Inc**  
 420 Megan Z Ave. Edgewater, FL 32132 Phone 386.423.2900 Fax 386.423.9187  
[www.brunswickcgp.com](http://www.brunswickcgp.com)